

Selection and Ordering data	Article No.
<b>Acoustic diagnostics unit SITRANS DA400</b> with local programming and display  ↗ Click on the Article No. for the online configuration in the PIA Life Cycle Portal.	<b>7MJ2400-</b> <b>A 0</b>
<b>Communication</b> • PROFIBUS DP • PROFIBUS PA	<b>1 A</b> <b>2 B</b>
<b>Explosion protection</b> • Without • With EEx ia/ib to ATEX <sup>1)</sup>	<b>A</b> <b>B</b>
<b>Application software</b> For continuous condition monitoring of positive displacement pumps for material flow monitoring in pipes, raceways and conveyors	<b>1</b> <b>2</b>
<b>Acoustic sensors for diagnostics unit SITRANS DA400</b>  ↗ Click on the Article No. for the online configuration in the PIA Life Cycle Portal.	<b>7MJ2000-1</b> <b>0 0</b>
<b>Explosion protection</b> • Without • With EEx ia to ATEX	<b>A</b> <b>B</b>
<b>Cable</b> (incl. pin and allen screw M6)  20 m 40 m 100 m	<b>B</b> <b>C</b> <b>F</b>
<b>Safety barriers for sensors</b> For rail mounting NS 32 and NS35/7.5 in non-hazardous areas Explosion-protected output circuit EEx ib	<b>7MJ2010-1AA</b>

<sup>1)</sup> Not in combination with trigger sensor.