Selection and Ordering data		Article No.
SITRANS RD200	↗	**7ML5740-**
A universal input, panel mount remote digital display for process instrumentation.		■■■■■ - ■ **A**
↗ Click on the Article No. for the online configuration in the PIA Life Cycle Portal.		
Input voltage		
85 ... 265 V AC, 50/60 Hz; 90 ... 265 V DC, 20 W max.	►⬟	**1**
12 ... 36 V DC; 12 ... 24 V AC, 6 W max.	⬟	**2**
Transmitter supply		
None	⬟	**A**
Single 24 V DC transmitter supply[1]	►⬟	**B**
Dual 24 V DC transmitter supply[1][2]		**C**
Output		
None	►⬟	**A**
2 relays	⬟	**B**
4 ... 20 mA output	⬟	**C**
Communication		
Modbus enabled	►⬟	**0**
Approvals		
CE, UL, $_{C}$UL	⬟	**1**
Display Size		
Standard	►⬟	**0**
2X option for 30.5 mm (1.2 inch) high, red LED	►⬟	**1**

[1] Available with input voltage option 1 only

[2] Available with output option C only

⬟ We can offer shorter delivery times for configurations designated with the Quick Ship Symbol ⬟. For details see page 9/5 in the appendix.

► Available ex stock when configured with the following options only: Input voltage: 1, Transmitter supply: B, Output : A, Communication: 0. For details see page 9/5 in the appendix.

Selection and Ordering data	Article No.
Operating Instructions	
English	**7ML1998-5JS01**
Spanish	**7ML1998-5JS21**
German Note: The Operating Instructions should be ordered as a separate line item. This device is shipped with the Siemens Milltronics manual DVD containing Quick Starts and Operating Instructions.	**7ML1998-5JS31**
Other Operating Instructions	
SITRANS RD Enclosures, English	**7ML1998-5JX01**
SITRANS RD Enclosures, German	**7ML1998-5JX31**
SITRANS RD Serial communications accessories, English	**A5E31979195**
SITRANS RD Serial communications accessories, German	**A5E31979197**
SITRANS RD Software, English	**7ML1998-5JW01**
SITRANS RD Software, German	**7ML1998-5JW31**

Selection and Ordering data	Article No.
Accessories	
SITRANS RD200 copy cable 2.1 m (7 ft)	**7ML1930-1BR**
SITRANS RD200 RS 232 serial adapter (copy cable included)	**7ML1930-1BS**
SITRANS RD200 RS 422/485 serial adapter (copy cable included)	**7ML1930-1BT**
RS 232 to RS 422/485 isolated converter	**7ML1930-1BU**
RS 232 to RS 422/485 non-isolated converter	**7ML1930-1BV**
SITRANS RD200 RS 232 and RS 485 isolated multi-input adapter board	**7ML1930-1BW**
USB to RS 422/485 isolated converter	**7ML1930-1BX**
USB to RS 422/485 non-isolated converter	**7ML1930-1BY**
USB to RS 232 converter	**7ML1930-6AK**
RD Software CD for 1 ... 100 displays	**7ML1930-1CC**
Low cost polycarbonate plastic enclosure for 1 display	**7ML1930-1CF**
2 inch (5.08 cm) pipe mounting kit (zinc plated seal) only available with 7ML1930-1CF	**7ML1930-1BP**
2 inch (5.08 cm) pipe mounting kit (stainless steel, Type 304, EN 1.4301) only available with 7ML1930-1CF	**7ML1930-1BQ**
Thermoplastic enclosure	
For use with 1 display	**7ML1930-1CG**
For use with 2 displays	**7ML1930-1CH**
For use with 3 displays	**7ML1930-1CJ**
For use with 4 displays	**7ML1930-1CK**
For use with 5 displays	**7ML1930-1CL**
For use with 6 displays	**7ML1930-1CM**
Stainless steel enclosure (Type 304, EN 1.4301)	
For use with 1 display	**7ML1930-1CN**
For use with 2 displays	**7ML1930-1CP**
For use with 3 displays	**7ML1930-1CQ**
For use with 4 displays	**7ML1930-1CR**
For use with 5 displays	**7ML1930-1CS**
For use with 6 displays	**7ML1930-1CT**
Steel enclosure	
For use with 1 display	**7ML1930-1CU**
For use with 2 displays	**7ML1930-1CV**
For use with 3 displays	**7ML1930-1CW**
For use with 4 displays	**7ML1930-1CX**
For use with 5 displays	**7ML1930-1CY**
For use with 6 displays	**7ML1930-1DA**