

Selection and Ordering data		Article No.	
SITRANS Probe LU 2-wire, loop powered ultrasonic transmitter for level, volume and flow monitoring of liquids in open channels, storage vessels, and simple process vessels.		➤ 7ML5221-	
➤ Click on the Article No. for the online configuration in the PIA Life Cycle Portal.			
Enclosure/Cable Inlet			
Plastic (PBT), 1 x M20x1.5 and 1 x ½" NPT (no cable glands supplied)	➤ 0		
Plastic (PBT), 2 x M20x1.5 (includes 1 general purpose cable gland: 7ML1930-1AM)	➤ 1		
Plastic (PBT), 2 x ½" NPT (no cable glands supplied)	➤ 2		
Range/Transducer material			
6 m (20 ft), ETFE	➤ A		
6 m (20 ft), PVDF Copolymer	➤ B		
12 m (40 ft), ETFE	➤ C		
12 m (40 ft), PVDF Copolymer	➤ D		
Process connection			
2" NPT [(Taper), ANSI/ASME B1.20.1]	➤ A		
R 2" [(BSPT), EN 10226]	➤ B		
G 2" [(BSPP), EN ISO 228-1]	➤ C		
Communication/Output			
4 ... 20 mA, HART	➤ 1		
PROFIBUS PA	➤ 2		
Approvals			
General Purpose, FM, CSA _{US/C} , CE, RCM, KCC	➤ 1		
Non-incendive, FM Class I, Div. 2 Groups A,B,C,D T5 ¹⁾	➤ 4		
Intrinsically Safe, CSA/FM Class I, Div. 1, Groups A, B, C, D; Class II, Div. 1, Groups E, F, G; Class III T4 ²⁾	➤ 5		
Intrinsically Safe ATEX 1G / JECEx / INMETRO Ex ia IIC T4 Ga, RCM, KCC ²⁾	➤ 6		
Intrinsically Safe ATEX 1G / JECEx / INMETRO Ex ia IIC T4 Ga, RCM, KCC ³⁾	➤ 7		
Intrinsically safe, CSA/FM Class I, Div. 1, Groups A, B, C, D; Class II, Div. 1 Groups E, F, G; Class III T4 ³⁾	➤ 8		

¹⁾ Available with Enclosure/Cable Inlet option 2 only.

²⁾ Available with communication option 2 only.

³⁾ Available with communication option 1 only.

◆ We can offer shorter delivery times for configurations designated with the Quick Ship Symbol ◆. For details see page 9/5 in the appendix.

1) Available with Enclosure/Cable Inlet option 2 only.

2) Available with communication option 2 only.

3) Available with communication option 1 only.

➤ We can offer shorter delivery times for configurations designated with the Quick Ship Symbol ➤. For details see page 9/5 in the appendix.

Selection and Ordering data	Order code
Further designs	
Please add "-Z" to Article No. and specify Order code(s).	
Stainless steel tag [69 x 50 mm (2.71 x 1.97 inch)]: Measuring-point number/identification (max. 27 characters) specify in plain text	➤ Y15
Operating Instructions for HART/mA device	Article No.
English	A5E32337695
French	7ML1998-5HT11
German	A5E34957881
Note: The Operating Instructions should be ordered as a separate item on the order.	
Additional Multi-language Quick Start manual This device is shipped with the Siemens Milltronics manual DVD containing the ATEX Quick Start and Operating Instructions library.	A5E32168031
Operating Instructions for PROFIBUS PA device	
English	A5E32337708
German	A5E34957884
Note: The Operating Instructions should be ordered as a separate item on the order.	
Additional Multi-language Quick Start manual This device is shipped with the Siemens Milltronics manual DVD containing the ATEX Quick Start and Operating Instructions library.	A5E32081626
Accessories	
Handheld programmer, Intrinsically Safe, EEx ia	7ML5830-2AH
Handheld programmer, General Purpose approvals	7ML1830-2AN
Handheld programmer, Infrared, Intrinsically Safe, PROFIBUS PA	7ML5830-2AJ
HART modem/USB (for use with a PC and SIMATIC PDM)	7MF4997-1DB
2" NPT locknut, plastic	7ML1830-1DT
2" BSPT locknut, plastic	7ML1830-1DQ
3" ASME, DN 65 PN 10, JIS 10K 3B ETFE Flange adapter for 2" NPT	7ML1830-1BT
3" ASME, DN 65 PN 10, JIS 10K 3B ETFE Flange adapter for 2" BSPT	7ML1830-1BU
One General Purpose polymeric cable gland M20x1.5, rated for -20 ... +80 °C (-4 ... +176 °F)	7ML1930-1AM
One metallic cable gland M20x1.5, rated -40 ... +80 °C (-40 ... +176 °F) for General Purpose or ATEX EEx e installations (available for HART only)	7ML1930-1AP
One metallic cable gland M20x1.5, rated -40 ... +80 °C (-40 ... +176 °F) with integrated shield connection (available for PROFIBUS PA)	7ML1930-1AQ
Probe LU, rock guard/sunshield kit, 304 stainless steel	7ML1930-1GH
SITRANS RD100, loop powered display - see Chapter 7	7ML5741-...
SITRANS RD200, universal input display with Modbus conversion - see Chapter 7	7ML5740-...
SITRANS RD300, dual line display with totalizer and linearization curve and Modbus conversion - see Chapter 7	7ML5744-...
SITRANS RD500 web, universal remote monitoring solution for instrumentation - see Chapter 7	7ML5750-...
For applicable back up point level switch see point level measurement section.	
Spare Parts	
Plastic lid	7ML1830-1KB